

**pH ENHANCED MEAT COMPOSITION AND METHOD  
FOR PRODUCING A pH ENHANCED MEAT COMPOSITION**

**INVENTOR:**


**ELDON ROTH**

"Express Mail" Mailing label number EL724187763US

Date of Deposit: April 12, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Services "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box Patent Applications, Washington, DC 20231

Reg. No. 32,124, Russell D. Culbertson

A handwritten signature in dark ink, appearing to read 'R. Culbertson', is written over a horizontal line.

1 pH ENHANCED MEAT COMPOSITION AND METHOD  
2 FOR PRODUCING A pH ENHANCED MEAT COMPOSITION  
3  
4  
5

6 CROSS-REFERENCE TO RELATED APPLICATION

7 This application is related to U.S. Patent Application No. 09/286,699, filed April 6,  
8 1999, entitled "APPARATUS FOR TREATING AMMONIATED MEATS" (as amended),  
9 now United States Patent No. 6,142,067, and to U.S. Patent Application No. 09/579,783,  
10 filed May 26, 2000, entitled "METHOD FOR TREATING AMMONIATED MEATS" now  
11 United States Patent No. 6,406,728. The entire content of each of these applications is  
12 incorporated herein by this reference.  
13

14 TECHNICAL FIELD OF THE INVENTION

15 The invention relates to meat products and meat processing. More particularly, the  
16 present invention relates to a pH enhanced comminuted meat composition and a method for  
17 producing a pH enhanced comminuted meat composition.  
18

19 BACKGROUND OF THE INVENTION

20 It has been found that modifying the pH of a meat product with ammonia may  
21 significantly reduce the live microbe content in the meat. This is particularly the case when  
22 the pH enhanced meat product is physically manipulated in a frozen state. Ammoniated meat  
23 products may also have other desirable characteristics unrelated to reduced microbe count.

1 It is also known to apply aqueous ammonia (ammonium hydroxide solution in water) or  
2 gaseous ammonia to large cuts of meat. The 1976 publication to Smol'skii et al. entitled  
3 "Method for Storage of Meat" discloses applying gaseous or aqueous ammonia to large cuts of  
4 meat to greatly increase the pH at a surface of the meat. That publication indicates that  
5 treating the large cuts of meat in this fashion helps preserve the meat in cold storage. United  
6 States Patent No. 3,023,109 to Hines shows applying gaseous ammonia to cuts of red meat to  
7 produce a bright red color in the meat.

8 In order to produce the desired effects in an ammoniated meat product made up of  
9 comminuted meat, it is necessary to ensure a consistent pH adjustment or enhancement  
10 throughout the mass of comminuted meat. The problem of ensuring a consistent pH adjustment  
11 in comminuted meats is addressed in related U.S. patent application 09/286,699, now U.S.  
12 Patent No. 6,142,067, and application No. 09/579,783, now U.S. Patent No. 6,446,720

13 \_\_\_. These documents disclose the process of first comminuting meat, exposing the  
14 comminuted meat to gaseous or aqueous ammonia, and then further comminuting the resulting  
15 ammoniated meat with a suitable comminuting device such as a grinder or bowl chopper. This  
16 process has been shown to help ensure a consistent pH adjustment throughout the comminuted  
17 meat product and to help eliminate any residual ammonia odor in the resulting product.

18 These prior related applications by the present inventor did not address the application  
19 of ammonia in situations where it is either unnecessary or undesirable to further comminute the  
20 meat after the application of ammonia. This is the case with meat batters for producing  
21 sausage or hotdogs, and is also the case in certain processes for producing restructured meat

1 products. In the case of meat batters for producing sausage or hotdogs, it is unnecessary to  
2 further comminute the batter. Restructured meat products such as restructured beef and ham,  
3 for example, may be produced by taking relatively large chunks of meat and mixing the large  
4 chunks with a finely comminuted meat paste. The meat paste in the mixture is used as a binder  
5 to help bind the larger chunks of meat together to produce the final restructured product. In  
6 the case of these types of restructured meat products, it is undesirable to further comminute the  
7 chunk/paste mixture since comminuting the mixture reduces the size of the relatively large  
8 chunks.

#### 10 SUMMARY OF THE INVENTION

11 It is an object of the present invention to provide a method for producing a  
12 comminuted, pH enhanced meat composition which does not require that the meat be  
13 comminuted further after the pH modifying material is added. Another object of the invention  
14 is to provide a pH enhanced meat composition produced according to the present method.

15 The present method includes increasing the moisture content of a comminuted meat  
16 composition to produce a moisture enhanced meat composition. The method also includes  
17 producing an ammonium hydroxide solution in the meat composition. Mechanical action is  
18 preferably applied to the meat composition after or concurrently with producing the ammonium  
19 hydroxide solution in the composition. The resulting pH enhanced meat composition may be  
20 used as a meat batter which may be combined with other material or used alone for producing  
21 hotdogs, sausages, or restructured meat products.

1           Moisture content in the comminuted meat may be increased by simply adding liquid  
2   water or ice to an initial comminuted meat composition or to a meat composition that has been  
3   exposed to ammonia. Where liquid water is added, the water may be potable water alone or a  
4   solution of ammonium hydroxide in water, that is, aqueous ammonia. In the latter case the  
5   step of adding the water/ammonium hydroxide solution not only increases the moisture content  
6   of the initial meat composition but also concurrently produces the desired ammonium  
7   hydroxide solution in the meat composition. When the moisture content in the initial meat  
8   composition is increased by adding water with no ammonium hydroxide content, the  
9   ammonium hydroxide solution may be created by contacting the moisture enhanced meat  
10   composition with ammonia gas. Contact with the ammonia gas allows the ammonia to go into  
11   solution in the water associated with the moisture enhanced meat composition. Alternatively,  
12   the ammonium hydroxide solution in the meat composition may be created as water is added to  
13   comminuted meat which has already been exposed to ammonia.

14           "Mechanical action" as used in this disclosure and the accompanying claims means  
15   producing relative movement within the mass of moisture enhanced meat. This mechanical  
16   action may be applied in any number of ways within the scope of the invention. For example,  
17   the moisture enhanced meat composition may be put in a suitable mechanical mixer or blender  
18   having paddles or other mechanical elements which are driven through the mass of moisture  
19   enhanced meat composition. Alternatively, a gas may be directed through a mass of moisture  
20   enhanced meat composition. The injected gas produces bubbles which displace the meat as the  
21   bubbles work their way through the meat composition. This displacement caused by the gas

1 bubbles produces mechanical action within the scope of the invention. Displacing the meat  
2 composition through a conduit may also produce the desired mechanical action in the meat  
3 composition depending upon the flow rate, nature of the meat composition, and the diameter of  
4 the conduit.

5 These and other objects, advantages, and features of the invention will be apparent  
6 from the following description of the preferred embodiments, considered along with the  
7 accompanying drawings.

#### 8 9 BRIEF DESCRIPTION OF THE DRAWINGS

10 Figure 1 is a flow chart showing the method steps according to the present invention.

11 Figure 2 is a diagrammatic representation of an apparatus for performing the method  
12 shown in Figure 1.

13 Figure 3 is a diagrammatic representation of an alternate apparatus for performing the  
14 method shown in Figure 1.

#### 15 16 DESCRIPTION OF THE PREFERRED EMBODIMENTS

17 Referring to Figure 1, the invention includes two basic steps shown in dashed box 10.  
18 One basic step comprises increasing the moisture content in a comminuted meat to produce a  
19 moisture enhanced meat composition as shown at process block 12. The other basic step  
20 comprises producing an ammonium hydroxide solution in the meat composition as shown at  
21 process block 14 in Figure 1. Another basic step which may be helpful, but not necessary, is

1 to apply mechanical action to the moisture enhanced meat composition after producing the  
2 ammonium hydroxide solution in the meat composition. In some cases, mechanical action may  
3 also be applied concurrently with producing the ammonium hydroxide solution in the meat  
4 composition. The application of mechanical action is shown at process block 16 in Figure 1.

5 The process starts with an initial comminuted meat and may be performed as a  
6 continuous or batch process. The initial comminuted meat may be beef, pork, lamb, mutton,  
7 poultry, fish, or a combination of any of these types of meat. In addition to actual meat  
8 protein or muscle, the initial comminuted meat will commonly include some level of fat  
9 content depending upon the desired final product. Spices, seasonings, fillers, or other  
10 materials may also be included in the initial comminuted meat. Alternatively, these other  
11 materials may be added after the steps shown at process blocks 12 and 14 in Figure 1.

12 The invention is particularly useful in connection with meat batters which may be used  
13 to produce hotdogs, sausage, or restructured meat products. The meat batter may comprise the  
14 initial comminuted meat, or a meat batter may be produced from the pH enhanced meat  
15 composition resulting from the steps shown at blocks 12 and 14 in Figure 1. The nature of the  
16 meat batter will depend upon the nature of the product to be produced. For example, finely  
17 textured hot dog and sausage batter will generally be made up of finely comminuted meats.  
18 Batter for producing restructured meat may include relatively large chunks of meat together  
19 with finely comminuted meat or meat paste. The relatively large chunks of meat may have a  
20 minimum dimension of more than one half (0.5) inch.

1           The present invention may be applied to substantially any initial meat composition  
2       which is at least partially made up of "small" pieces of comminuted meat. As used in this  
3       disclosure and the accompanying claims the term "small" when referring to comminuted meat  
4       pieces shall mean pieces small enough in size so that the pH of the entire piece of material may  
5       be changed by the ammonium hydroxide solution in the moisture enhanced meat composition.  
6       For uncooked meat, at least one dimension of such a piece of meat will be not more than  
7       approximately one-half (0.5) inch. Thus, as set out in this disclosure and the accompanying  
8       claims, a "small" piece of comminuted meat comprises any piece of meat having at least one  
9       dimension of not more than approximately one-half (0.5) inch. Preferably, the entire initial  
10      meat composition is made up of small pieces of comminuted meat. If a restructured meat  
11      batter calls for larger pieces of meat in the meat batter, those larger pieces are preferably added  
12      after the present process is applied to a composition of small comminuted meat pieces. Also,  
13      the term "large" when referring to comminuted meat pieces will mean pieces having a  
14      minimum dimension over one-half (0.5) inch.

15           The two basic steps shown at process blocks 12 and 14 may be accomplished in a  
16      number of different ways within the scope of the present invention. One preferred process  
17      includes two discrete steps. In one form of the invention the first step includes adding water  
18      (in liquid form and/or as ice) to the initial comminuted meat, and then producing the  
19      ammonium hydroxide solution in the moisture enhanced meat composition as a separate step  
20      after adding water. In this two-step process, the step of producing the ammonium hydroxide  
21      solution in the moisture enhanced meat composition may be performed by placing ammonia gas



1 in contact with the meat composition. Particularly where mechanical action is applied to the  
2 moisture enhanced meat composition as shown at process block 16 in Figure 1, the ammonia  
3 gas need not be at an elevated pressure in order to produce the desired ammonium hydroxide  
4 solution in the meat composition. Rather, ammonia from the gas readily goes into solution in  
5 the water associated with the moisture enhanced meat composition to produce the ammonium  
6 hydroxide solution.

7 In an alternate form of the invention, an initial comminuted meat product may be  
8 exposed to ammonia first and then water may be added to the ammoniated meat. In this case,  
9 the ammonium hydroxide solution is produced as the previously applied ammonia goes into  
10 solution in the added water. Particularly in this form of the invention care should be taken to  
11 ensure that the initially applied ammonia does not locally denature the comminuted meat. A  
12 gradual addition of ammonia to the meat composition is preferred to avoid locally denaturing  
13 the meat. It may be necessary to apply ammonia and then water in a number of cycles to effect  
14 the desired overall pH adjustment without denaturing portions of the meat.

15 Alternatively to two discrete steps, moisture may be added to the initial comminuted  
16 meat composition at the same time the desired ammonium hydroxide solution is produced in  
17 the meat composition. In this alternative implementation, an ammonium hydroxide solution is  
18 added to the initial meat composition. The water in the solution increases the moisture content  
19 in the initial comminuted meat to produce the moisture enhanced meat composition. Also, it is  
20 possible to combine the two-step approach and single step approach. That is, water may be  
21 added to an initial comminuted meat in a separate step and then the desired ammonium

hydroxide solution may be produced in the meat composition by adding an ammonium hydroxide solution. Of course, adding ammonium hydroxide solution not only produces a desired solution in the meat composition but also further enhances the moisture content in the composition. Also, ammonium hydroxide solution may be added to the initial meat composition and the concentration of ammonium hydroxide solution may be increased later by contacting the composition with ammonia gas.

In any of these alternatives, the resulting comminuted meat composition has an enhanced pH. This enhanced pH has been found beneficial in meat products. The water added according to the invention serves to distribute the ammonia throughout the product and help eliminate any undesirable ammonia odor in the resulting uncooked composition and any residual ammonia odor or taste in the cooked product.

The application of mechanical action shown at process block 16 in Figure 1 is helpful in certain circumstances to distribute the water and desired ammonium hydroxide solution throughout the moisture enhanced meat composition. Mechanical action may also be helpful in producing the desired meat batter by helping extract myosin-type proteins out of the meat pieces as is known in the art. The mechanical action according to the invention may be applied with a paddle or other element driven through a mass of the meat composition. An example of a paddle-type apparatus for applying mechanical action is shown in Figure 2. Alternatively, a gas may be injected into the mixture to force the desired movement in the material. This gas injection-type of mechanical action will be discussed below with reference to the apparatus shown in Figure 3.

1           The process according to the invention may be performed under a wide range of  
2 parameters. For example, the temperature of the meat composition should be a temperature  
3 high enough to ensure that at least some liquid water exists in the meat composition. Also, the  
4 temperature of the meat composition at the time the ammonium hydroxide solution is produced  
5 in the material should be high enough to allow the meat composition to be workable or  
6 flowable. Meat composition temperatures generally above 28 degrees Fahrenheit will be  
7 sufficient for most circumstances. The maximum temperature of the meat composition for the  
8 purposes of the present invention will be limited generally by the temperature at which the  
9 meat in the composition begins to cook or set. That is, the temperature of the meat  
10 composition should be low enough that the meat in the composition does not cook or is not  
11 cooked in the course of the present process.

12           Due in part to the solubility of ammonia in water, only a minimal moisture increase to  
13 the initial comminuted meat composition is necessary according to the invention. Generally,  
14 the increase in moisture content shown as process block 12 in Figure 1 may be any increase  
15 that raises the moisture content above that naturally occurring in the initial meat composition.  
16 For example, ground beef containing 30% fat will have a moisture (water) content of  
17 approximately 65% by weight in the overall material. A moisture increase within the scope of  
18 the invention for such a meat composition may comprise an increase which raises the moisture  
19 content over 65%. Where the initial meat composition has less fat content, 2% fat content for  
20 example, the natural moisture content may be approximately 80% by weight. A moisture  
21 increase within the scope of the invention for such a meat composition may comprise an

1 increase which raises the moisture content over 80%. It will be noted that a higher moisture  
2 content in the moisture enhanced composition generally makes it easier to produce a relatively  
3 higher pH in the meat composition.

4 The concentration of ammonium hydroxide solution produced in the moisture enhanced  
5 comminuted meat composition will depend upon the nature of the final product, since the pH  
6 level of a meat affects the taste of the cooked product. Where the final comminuted product is  
7 substantially unseasoned meat, it will generally be desirable to ensure that the pH of the  
8 uncooked meat composition is maintained below about 7.0. This is compared to a pH of about  
9 5.5 to 5.7 for regular ground beef. However, where the final product is highly seasoned, the  
10 pH of the material may be raised to as much as 9.5 without damaging with the taste of the  
11 desired product. In every case, the amount of ammonium hydroxide solution produced in the  
12 moisture enhanced meat composition should be just enough to raise the pH of the resulting  
13 composition to the desired level. It is also desirable that the pH be consistent throughout the  
14 resulting meat composition. The mechanical action helps produce this relatively consistent pH  
15 level throughout the material.

16 The time required to produce the desired pH level in the moisture enhanced meat  
17 composition will depend upon how the solution is produced, the moisture content in the  
18 composition, and the temperature of the meat composition. Where the ammonium hydroxide  
19 solution is produced by allowing ammonia gas to go into solution in water in the moisture  
20 enhanced meat composition, relatively long periods of ammonia gas contact and mechanical  
21 action may be required to produce the desired pH increase. Of course, higher concentrations

1 of ammonia gas will result in relatively faster ammonium hydroxide production as compared to  
2 lower concentrations of ammonia gas. In any event, the process of allowing ammonia gas to  
3 go into solution slowly from ammonia gas as mechanical action is applied to the comminuted  
4 meat is most suitable for finely comminuted meat batters. These batters include those made up  
5 of meat pieces having a maximum dimension of approximately one-eighth (0.125) inch or less.  
6 Alternatively, where the moisture increase and ammonium hydroxide solution in the  
7 comminuted meat is produced by adding ammonium hydroxide solution to the comminuted  
8 meat, or by adding gaseous or liquid ammonia and then water, the pH increase may be very  
9 rapid and the time required by the process is dictated by the time required to ensure that the  
10 material is thoroughly mixed to provide a consistent pH change throughout the material.

11 Since the pH enhancement process according to the invention is particularly applicable  
12 to meat batters used to produce hotdogs, sausage, or restructured meat products, forms of the  
13 invention include product forming operations along with the pH enhancement steps. The step  
14 of forming the meat batter into a desired shape and setting the material in that shape is shown  
15 at process block 18 in Figure 1.

16 Many processes for forming a meat batter into a desired shape and then setting the  
17 batter in that shape are known in the art. Generally, the forming and setting steps may  
18 comprise any forming and setting steps which may be applied to meat batters. For certain  
19 types of restructured meat products for example, the step of forming the product into a desired  
20 shape may include containing the batter in a flexible container or bag and then placing the bag  
21 in a mold having the desired shape. The halves of the mold are then pressed together under

1 high pressure to press the meat batter-filled bag into the desired shape as dictated by the shape  
2 of the mold. In some cases the pressure applied to the meat batter in the mold sets the batter in  
3 the desired shape. Also, the meat batter may be frozen or cooked in the mold to set the  
4 material in the desired shape. Alternatively, cooking or deep freezing may be performed on  
5 the formed meat composition after removal from the mold.

6 Other restructured meat products are formed during the cooking process. For example,  
7 a finely textured meat batter or emulsion may be formed into small pieces of meat resembling  
8 cooked ground beef by applying mechanical action to the batter as the batter is heated in a  
9 vessel. The invention also encompasses this forming and setting method.

10 The forming and setting step within the scope of the present invention may be  
11 performed somewhat differently for meat products such as hotdogs or sausages. In the case of  
12 hotdogs or sausages, the meat batter may be injected into an edible casing and the casing forces  
13 the meat batter into the desired shape. The filled and sealed hotdog or sausage casings may  
14 then be cooked and then distributed in a cooked/refrigerated form. Some types of sausage  
15 may alternatively be refrigerated in the uncooked form and distributed uncooked.

16 Figure 2 shows one preferred apparatus 19 for performing the method according to the  
17 present invention. The apparatus includes a vessel 20 for containing a mass of comminuted  
18 meat. The level of the comminuted meat is shown at "L" in Figure 2 for purposes of example.  
19 The vessel includes an outlet opening 21 at the bottom and a closed top 22. The closed top  
20 includes a purge vent 23 and a meat product inlet port 24. The apparatus 19 also includes an  
21 ammonia gas inlet 25 and a separate purge gas inlet 26 located in the vessel top 22. Of course,

1 those skilled in the art will readily appreciate that other access openings into vessel 20 may be  
2 helpful or necessary, but are omitted from the diagrammatic representation shown in Figure 2.

3 Two paddle assemblies 30 are mounted within vessel 20, each including a number of  
4 paddles 31. Each paddle assembly is driven about an axis extending generally perpendicular to  
5 the plane of the drawing sheet by a driving motor and transmission arrangement which is not  
6 shown in the figure. The two paddle assemblies 30 may be driven in counter rotating fashion  
7 with the assembly on the left driven clockwise or counter clockwise and the assembly on the  
8 right in Figure 2 driven in the opposite direction.

9 The apparatus shown in Figure 2 also includes an output pump or auger 34 connected to  
10 the outlet opening 21 at the bottom of vessel 20. Outlet pump 34 directs material from vessel  
11 20 through a conduit 35 to a forming/setting system 36. As discussed above, the  
12 forming/setting system may be any forming and setting arrangement suitable for the particular  
13 product being produced. For hotdogs or sausages for example, the forming/setting system 36  
14 may include a hotdog or sausage casing filling device and then a heating arrangement for  
15 cooking the raw hotdogs or sausages. Alternatively, forming/setting system 36 may include a  
16 system for filling flexible bags with meat batter and then placing the filled bags in a forming  
17 press to be pressed into a desired shape. This alternative may further include a cooking  
18 arrangement for cooking the formed product prior to freezing or refrigeration.

19 The apparatus shown in Figure 2 may receive a mass of comminuted meat through inlet  
20 port 24. The received material may already have water added or water may be added once the  
21 material is in vessel 20. In either case, ammonium hydroxide solution may be produced in the

1 moisture enhanced meat composition in vessel 20 by creating an ammonia atmosphere in the  
2 area above the meat level L, and by applying mechanical action to the moisture enhanced meat  
3 composition through paddle assemblies 30. The paddle assemblies 30 circulate the meat  
4 composition in the vessel and continuously expose new material to the ammonia gas at the top  
5 of the vessel. This contact between the ammonia gas and moisture enhanced meat composition  
6 allows ammonia to go into solution in the water contained in the batter to form the desired  
7 ammonia hydroxide solution. Once sufficient ammonium hydroxide has gone into solution to  
8 produce the desired pH in the meat composition, the meat composition may then be pumped to  
9 the forming/setting system 36 for forming into the desired products.

10 It will be appreciated that the pH enhanced meat composition produced according to the  
11 invention may be mixed with other material to form a final meat batter. This is particularly the  
12 case with some batters for producing restructured meat products. The process according to the  
13 invention may be applied to an initial meat composition comprising a finely comminuted meat,  
14 and then the resulting pH enhanced finely comminuted meat or meat paste may be combined  
15 with relatively large chunks of meat to produce the desired batter. In this case, the large  
16 pieces of meat may be added to the final pH enhanced composition in vessel 20, or may be  
17 added to the pH enhanced composition after it is removed from vessel 20.

18 The apparatus 19 in Figure 2 may also be used for first applying ammonia to an initial  
19 comminuted meat in vessel 20 and then adding water to the ammoniated meat. In this case, the  
20 ammonium hydroxide solution in the meat composition is produced as free ammonia on the  
21 ammoniated meat goes into solution in the added water. Paddle assemblies 30 may be operated



1 to ensure that the ammonium hydroxide solution is well distributed through the meat  
2 composition.

3 Figure 3 shows an alternate apparatus 40 for performing the method according to the  
4 invention. The apparatus in Figure 3 includes a vessel 41 having a top vent 42 and a bottom  
5 outlet opening 43. Vessel 41 also includes one or more feed ports 44 for feeding an initial  
6 comminuted meat or moisture enhanced meat composition into the vessel. The level the meat  
7 composition in vessel 41 is shown at "M" in Figure 3. Similar to Figure 2, the bottom outlet  
8 opening 43 is connected to a pump or auger 46 which is in turn connected to a conduit 47 for  
9 directing the meat composition to a forming/setting system 48.

10 Unlike the apparatus shown in Figure 2, mechanical action is applied in the apparatus  
11 of Figure 3 by injecting a suitable gas into the meat composition. The gas may be air,  
12 nitrogen, oxygen, or any other suitable gas or mixture of gases. Regardless of the type of gas  
13 used, the mixing gas is injected preferably through a manifold 50 at the bottom of vessel 41  
14 and allowed to bubble up through the meat composition. Eventually the injected gas exits  
15 vessel 41 through top vent 42. The injection pressure must be a pressure higher than the  
16 hydrostatic pressure exerted by the column of material in the vessel in order to allow the gas to  
17 flow into vessel 41. In this form of the invention the movement of the gas bubbles through the  
18 meat composition produces the desired mechanical action in the comminuted meat composition.

19 In the form of the invention shown in Figure 3, the desired ammonium hydroxide  
20 solution may be produced in the meat composition by injecting ammonia gas into the bottom of  
21 vessel 41 through ammonia manifold 51. Although this separate manifold 51 is shown for the

1 ammonia gas, it will be appreciated that the ammonia may be included in the gas used to  
2 produce the mechanical action in the comminuted material. Alternatively, the ammonium  
3 hydroxide solution in the comminuted meat may be produced by adding aqueous ammonia to  
4 the comminuted material in the vessel through a suitable conduit into the vessel. As with the  
5 apparatus shown in Figure 2, water may be added to the meat material in the vessel 41 through  
6 a suitable conduit, or may be added prior to reaching the vessel.

7 The above described preferred embodiments are intended to illustrate the principles of  
8 the invention, but not to limit the scope of the invention. Various other embodiments and  
9 modifications to these preferred embodiments may be made by those skilled in the art without  
10 departing from the scope of the following claims.